

Package: savvy (via r-universe)

October 14, 2026

Title A Simple Wrapper of 'savvy-cli' Command
Version 0.0.5
Description Generates the C and R wrappers for the Rust-powered R package using the savvy framework.
License MIT + file LICENSE
URL <https://github.com/yutannihilation/savvy>
Encoding UTF-8
Roxygen list(markdown = TRUE)
RoxygenNote 7.3.2
Imports jsonlite, pkgbuild
Suggests testthat (>= 3.0.0)
Config/testthat/edition 3
Repository <https://yutannihilation.r-universe.dev>
Date/Publication 2025-04-12 12:47:49 UTC
RemoteUrl <https://github.com/yutannihilation/savvy-helper-R-package>
RemoteRef HEAD
RemoteSha 17f7992f974c446869f89efaf4a0e3f5de4cc3ad

Contents

download_savvy_cli	2
savvy_extract_tests	2
savvy_init	2
savvy_source	3
savvy_update	3
savvy_version	4
Index	5

download_savvy_cli	<i>Update 'savvy-cli'</i>
--------------------	---------------------------

Description

Update 'savvy-cli'

Usage

```
download_savvy_cli()
```

savvy_extract_tests	<i>Execute savvy-cli extract-tests</i>
---------------------	--

Description

Execute savvy-cli extract-tests

Usage

```
savvy_extract_tests(path = "./src/rust/")
```

Arguments

path	Path to the root of a Rust crate.
------	-----------------------------------

savvy_init	<i>Execute 'savvy-cli init'</i>
------------	---------------------------------

Description

Execute 'savvy-cli init'

Usage

```
savvy_init(path = ".", verbose = TRUE)
```

Arguments

path	Path to the root of an R package
verbose	If TRUE, show all the output from savvy-cli.

`savvy_source`*Compile Rust Code And Load*

Description

Compile Rust Code And Load

Usage

```
savvy_source(  
  code,  
  use_cache_dir = TRUE,  
  env = parent.frame(),  
  dependencies = list(),  
  clean = NULL  
)
```

Arguments

<code>code</code>	Rust code to compile.
<code>use_cache_dir</code>	If TRUE, reuse and override the cache dir to avoid re-compilation. This is an expert-only option.
<code>env</code>	The R environment where the R wrapping functions should be defined.
<code>dependencies</code>	List of dependencies. (e.g. <code>list(once_cell = list(version = "1"))</code>) at the end of the R session.
<code>clean</code>	If TRUE, remove the temporary R package used for compilation

`savvy_update`*Execute 'savvy-cli update'*

Description

Execute 'savvy-cli update'

Usage

```
savvy_update(path = ".", verbose = TRUE)
```

Arguments

<code>path</code>	Path to the root of an R package
<code>verbose</code>	If TRUE, show all the output from savvy-cli.

savvy_version	<i>Execute 'savvy-cli -version'</i>
---------------	-------------------------------------

Description

Execute 'savvy-cli -version'

Usage

savvy_version()

Index

`download_savvy_cli`, [2](#)

`savvy_extract_tests`, [2](#)

`savvy_init`, [2](#)

`savvy_source`, [3](#)

`savvy_update`, [3](#)

`savvy_version`, [4](#)