

Package: string2path (via r-universe)

July 1, 2024

Title Rendering Font into 'data.frame'

Version 0.1.7.9000

Description Extract glyph information from font data, and translate the outline curves to flattened paths or tessellated polygons. The converted data is returned as a 'data.frame' in easy-to-plot format.

License MIT + file LICENSE

Depends R (>= 4.2)

Imports tibble, cli

Suggests testthat (>= 3.0.0)

URL <https://yutannihilation.github.io/string2path/>,
<https://github.com/yutannihilation/string2path>

BugReports <https://github.com/yutannihilation/string2path/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

SystemRequirements Cargo (Rust's package manager), rustc

Biarch true

Config/testthat/edition 3

Config/string2path/MSRV 1.65.0

Repository <https://yutannihilation.r-universe.dev>

RemoteUrl <https://github.com/yutannihilation/string2path>

RemoteRef HEAD

RemoteSha d2241bccf72e075666f7a1f7219c5e20f325446b

Contents

dump_fontdb	2
string2path	2

Index	5
--------------	----------

 dump_fontdb

Dump the Font Database

Description

For debugging purposes, extract all font faces on the font database which 'string2path' uses internally.

Usage

```
dump_fontdb()
```

Value

A tibble() containing these columns:

source The source file of the font face.

index The index of the font face within the source.

family The font family of the face.

weight The weight of the face.

style The style of the face.

 string2path

Convert a String to Paths

Description

string2path() converts a text to the paths of the width-less outlines of each glyph. string2stroke() converts a text to the paths of the outlines, with the specified line width, of each glyph. string2fill() converts a text to the paths of the filled polygon of each glyph.

Usage

```
string2path(
  text,
  font,
  font_weight = c("normal", "thin", "extra_thin", "light", "medium", "semibold", "bold",
    "extra_bold", "black"),
  font_style = c("normal", "italic", "oblique"),
  tolerance = 5e-05
)

string2stroke(
  text,
```

```

    font,
    font_weight = c("normal", "thin", "extra_thin", "light", "medium", "semibold", "bold",
      "extra_bold", "black"),
    font_style = c("normal", "italic", "oblique"),
    tolerance = 5e-05,
    line_width = 0.03
  )

string2fill(
  text,
  font,
  font_weight = c("normal", "thin", "extra_thin", "light", "medium", "semibold", "bold",
    "extra_bold", "black"),
  font_style = c("normal", "italic", "oblique"),
  tolerance = 5e-05
)

```

Arguments

text	A text to convert to paths.
font	A font family (e.g. "Arial") or a path to a font file (e.g. "path/to/font.ttf").
font_weight	A font weight.
font_style	A font style.
tolerance	Maximum distance allowed between the curve and its approximation. For more details, please refer to the documentation of the underlying Rust library .
line_width	Line width of strokes.

Value

A tibble() containing these columns:

x x position of the point on the path, scaled to x / line height. The left side of the first glyph is at x = 0.

y Y position of the point on the path, scaled to y / line height. The baseline of the first line is at y = 0.

glyph_id IDs to distinguish the glyphs.

path_id IDs to distinguish the groups of paths.

triangle_id IDs to distinguish the triangles. string2path() doesn't contain this column.

Examples

```

available_fonts <- dump_fontdb()

if (nrow(available_fonts) > 0) {
  family <- available_fonts$family[1]
  weight <- available_fonts$weight[1]
  style <- available_fonts$style[1]
}

```

```
# string2path() converts a text to paths
d_path <- string2path("TEXT", family, weight, style)
if (nrow(d_path) > 0) {
  plot(d_path$x, d_path$y)
  for (p in split(d_path, d_path$path_id)) {
    lines(p$x, p$y)
  }
}

# string2stroke() converts a text to strokes
d_stroke <- string2stroke("TEXT", family, weight, style)
if (nrow(d_stroke) > 0) {
  plot(d_stroke$x, d_stroke$y)

  # The stroke is split into triangles, which can be distinguished by `triangle_id`
  set.seed(2)
  for (p in split(d_stroke, d_stroke$triangle_id)) {
    polygon(p$x, p$y, col = rgb(runif(1), runif(1), runif(1), 0.8))
  }
}

# string2fill() converts a text to filled polygons
d_fill <- string2fill("TEXT", family, weight, style)
if (nrow(d_fill) > 0) {
  plot(d_fill$x, d_fill$y)

  # The polygon is split into triangles, which can be distinguished by `triangle_id`
  set.seed(2)
  for (p in split(d_fill, d_fill$triangle_id)) {
    polygon(p$x, p$y, col = rgb(runif(1), runif(1), runif(1), 0.8))
  }
}
}
```

Index

`dump_fontdb`, [2](#)

`string2fill (string2path)`, [2](#)

`string2path`, [2](#)

`string2stroke (string2path)`, [2](#)